

Pocket Meters

A broad range for all your environmental needs



- Water resistant
- 100% buoyancy
- Dual level display
- Stability indicator
- 2-Button operation
- ATC
- Auto buffer recognition
- Replaceable electrode
- % battery charge

| SPECIFICATIONS | | ORP HI 98120 | pH/ORP Combo HI 98121 | pHep*4 HI 98127 | pHep*5 HI 98128 | Combo HI 98129 | Combo HI 98130 | DiST*5 HI 98311 | DiST*6 HI 98312 |
|--|-----------------------------|-----------------|--------------------------|--------------------|--------------------|-------------------|-------------------|--------------------|--------------------|
| Range | pH 0.0 to 14.0 | | | | | | | | |
| | pH 0.00 to 14.00 | | | | | | | | |
| | EC 0 to 3999 μ S/cm | | | | | | | | |
| | EC 0.00 to 20.00 mS/cm | | | | | | | | |
| | TDS 0 to 2000 ppm | | | | | | | | |
| | TDS 0.00 to 10.00 ppt | | | | | | | | |
| | ORP \pm 1000 mV | | | | | | | | |
| | Temperature 0.0 to 60.0°C | | | | | | | | |
| | Temperature 32.0 to 140.0°F | | | | | | | | |
| Resolution | 0.1 pH | | | | | | | | |
| | 0.01 pH | | | | | | | | |
| | 1 μ S/cm EC | | | | | | | | |
| | 0.01 mS/cm EC | | | | | | | | |
| | 1 ppm TDS | | | | | | | | |
| | 0.01 ppt TDS | | | | | | | | |
| | 1 mV ORP | | | | | | | | |
| | 0.1°F/°C | | | | | | | | |
| Accuracy (@20°C/68°F) | \pm 0.1 pH | | | | | | | | |
| | \pm 0.05 pH | | | | | | | | |
| | \pm 2% F.S. EC/TDS | | | | | | | | |
| | \pm 2 mV ORP | | | | | | | | |
| | \pm 0.5 °C | | | | | | | | |
| | \pm 1 °F | | | | | | | | |
| Calibration* | pH Automatic* | | | | | | | | |
| | EC/TDS Automatic** | | | | | | | | |
| Automatic Temperature Compensation | | | | | | | | | |
| Battery Type (4) 1.5V | | | | | | | | | |
| Battery Life (hours) | 300 | 250 | 300 | 300 | 100 | 100 | 100 | 100 | |
| Battery Error Prevention System (BEPS) | | | | | | | | | |
| Auto-off after 8 minutes | | | | | | | | | |

*1 or 2 points with 2 sets of memorized buffers, (pH 4.01/ 7.01/10.01 or pH 4.01/6.86/9.18)

**1 point at 1413 μ S/cm or 12.88 mS/cm